

# LORD® LokRelease™ 100EZ Mold Release

## Description

LORD® LokRelease™ 100EZ mold release is a fast curing, nontransferable release agent designed for use with molded elastomers, including EPDM, natural rubber, nitrile and neoprene. It provides a semi-permanent, anti-stick surface coating for fast, easy part removal from molds.

## Features and Benefits

**Process Enhancer** – provides quick, easy part release from molds; single application allows multiple molding cycles; improves molding efficiency in many processes including injection, compression and transfer molding.

	Pure Elastomer	Elastomer-to-Metal
Injection	•	
Compression	•	•
Transfer	•	

**Improved Appearance** – reduces defects caused by sticking; nontransferable to elastomer compound; does not interfere with compound chemistry.

**Environmentally Recommended** – contains no Class I or Class II ozone depleting substances; contains no chlorofluorocarbon (CFC) or hydrochlorofluorocarbon (HCFC) propellants; contains no 1,1,1 trichloroethane or methylene chloride.

## Application

**Surface Preparation** – Remove mold release residue and other contaminants from surface of the mold prior to application.

**Applying** – Spray two or three light coatings of mold release on entire mold surface. Mold release can be applied to either hot or cold molds.

**Drying/Curing** – LORD LokRelease 100EZ mold release will quickly bond to heated mold surfaces [ $\geq 150^{\circ}\text{F}$  ( $66^{\circ}\text{C}$ )] within 5 minutes. Mold release will bond at room temperature if allowed to cure on mold surfaces for 1-2 hours before molding process.

If spot sticking occurs after molding, mold release coating can be “touched-up” by spraying LORD LokRelease 100EZ mold release directly on the sticking area and allowing time to cure.

## Typical Properties\*

Appearance	Colorless Aerosol
Density	
lb/gal	5.92
(g/cm <sup>3</sup> )	(0.71)
Dispersing Medium	Propellant/Solvent

\*Data is typical and not to be used for specification purposes.

# LORD TECHNICAL DATA

**Cleanup** – If necessary, mold release coating can be removed from mold surface by gentle-abrasive (plastic) bead blasting.

## Shelf Life/Storage

Shelf life is three years from date of manufacture when stored at room temperature [ $<120^{\circ}\text{F}$  ( $<49^{\circ}\text{C}$ )] in original, unopened container. Do not store or use near heat, sparks or open flame. Keep container closed when not in use.

## Cautionary Information

Before using this or any LORD product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

*For industrial/commercial use only.* Must be applied by trained personnel only. Not to be used in household applications. Not for consumer use.

Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. For formalized product specifications for specific product end uses, contact the Customer Support Center.

Information provided herein is based upon tests believed to be reliable. In as much as LORD Corporation has no control over the manner in which others may use this information, it does not guarantee the results to be obtained. In addition, LORD Corporation does not guarantee the performance of the product or the results obtained from the use of the product or this information where the product has been repackaged by any third party, including but not limited to any product end-user. Nor does the company make any express or implied warranty of merchantability or fitness for a particular purpose concerning the effects or results of such use.

LORD, LokRelease and "Ask Us How" are trademarks of LORD Corporation or one of its subsidiaries.

---

LORD provides valuable expertise in adhesives and coatings, vibration and motion control, and magnetically responsive technologies. Our people work in collaboration with our customers to help them increase the value of their products. Innovative and responsive in an ever-changing marketplace, we are focused on providing solutions for our customers worldwide ... Ask Us How.

### **LORD Corporation** **World Headquarters**

111 Lord Drive  
Cary, NC 27511-7923  
USA

### **Customer Support Center** (in United States & Canada)

+1 877 ASK LORD (275 5673)

[www.lord.com](http://www.lord.com)

For a listing of our worldwide locations, visit [LORD.com](http://LORD.com).

©2016 LORD Corporation OD DS4245 (Rev.2 10/16)

**LORD**  
AskUsHow™